



TEXO[®]
www.fasada.rs

IZJAVA O SVOJSTVIMA
(DECLARATION OF PERFORMANCE)

DECLARATION OF PERFORMANCE

In accordance with Regulation (EU) 305/2011 (Construction Product Regulation)

No: DOP-CE Fasaplast -001/2023

| | | | |
|---|--|----------------|---------------|
| 1. The unique identification code of the product-type | Fasaplast full and rajb | | |
| 2. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification, as foressen by the manufacturer | Plaster based on acrylic for indoor and outdoor applications | | |
| 3. Type, batch or serial number or any other element allowing identification of the construction product | Batch number and manufacture date are marked on the packing | | |
| 4. Name, registered trade name and contact address of the manufacturer | FASADA DOO Banovačka 66 22300 Stara Pazova, Srbija www.fasada.rs | | |
| 5. System of AVCP | System 4 | | |
| 6. Technical specification | EN 15824:2012, EAD 040083-00-0404 | | |
| 7. Declared performance: | | | |
| Adhesion to concrete substrate | ≥0.3 MPa | EN 1542-12 | EN 15824:2012 |
| Water vapur permeability | V2 | EN ISO 7783-11 | EN 15824:2012 |
| Capillary water absorpcion | W3 | EN 1062-3-18 | EN 15824:2012 |



TEXO[®]
www.fasada.rs

IZJAVA O SVOJSTVIMA
(DECLARATION OF PERFORMANCE)

| | | | |
|--|----------|--------------|--------------------|
| Reaction to fire ETICS MW (klasa) | A2-S1,d0 | EN 13238 | EAD 040083-00-0404 |
| Reaction to fire ETICS EPS (class) | B-s1, d0 | EN 13238 | EAD 040083-00-0404 |
| Thermal resistance ((m ² ·K)/W) | 0.02 | EN 1745:2002 | EN 15824:2012 |

8. Product is also component of external thermal insulation composite system with plaster

Texotherm EPS,ETA-23/460 -Test Institute for Construction Prague,No1020

Texotherm EPS,ETA-23/461-Test Institute for Construction Prague, No1020

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

The manufacturer listed in point 4 is solely responsible for issuing the declaration of properties. The declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Signed statement on behalf of the manufacturer



Radmila Jankovic

Engineer in the area of quality control and product development

In Stara Pazova, 22.04.2025

**TEXO**[®]

www.fasada.rs

IZJAVA O SVOJSTVIMA
(DECLARATION OF PERFORMANCE)**CE**FASADA d.o.o.
Banovačka 66, 22300 Stara Pazova
Srbija

23

Certificate of constancy performance
No.1020-CPR-020048333Certificate of constancy performance
No.1020-CPR-020048332

ETA 23/0461

ETA 23/0400

TEXOTHERM MW

TEXOTHERM EPS

EAD 040083-00-0404

EN 15824

Unique identification code of product: Fasaplast
Declaration of performance No: 001/2023

Fasaplast

Mortar based on organic binders for decoration and protection of facade and interior wall surfaces. Fasaplast it is certified for use in the External Thermal Insulation System (ETICS) Texotherm EPS and Texotherm MW.

| | |
|---|-----------|
| Adhesion to concrete substrate | ≥0.3 MPa |
| Water vapor permeability (class) | V2 |
| Capillary water absorption | W3 |
| Thermal resistance, Retics [(m ² ·K)/W] | ≥1.00 |
| Thermal resistance, Rrender [(m ² ·K)/W] | 0.02 |
| Reaction to fire ETICS MW (klasa): | A2-s1, d0 |
| Reaction to fire ETICS EPS (klasa): | B-s1, d0 |